

# Panel Mount Thermometer with Hi/LO Alarm

## Model: ST-9290D

Specifications	Description
Measuring range	-50°C ~ 300 °C (-58°F ~572 °F)
Accuracy	±1°C in the range of -30°C ~ 150°C, other: ±2°C
Resolution	0.1° in the range of -19.9°~ 199.9°, others : 1°
Response Time	1 second
LCD Display	48 (L) x 22(H) mm
Panel Size	62 (L) x 36.5 (H) x 14 (D) mm
External Sensor	ø3.5 x 46L mm
Cable length	1M
Battery	LR44/A76 or equivalent
Weight	52g
<b>Note: No waterproof function. Do not put in dishwashing machine for cleaning</b>	



## ST-9290D series have different functions offer:

- ST-9290D-1: °C/°F switch
- ST-9290D-2: Memory recalling (min/max) switch

## Standard Accessories:

- Sucker x 1
- White box x 1
- 1.5V A76 button cell x 1 or equivalent
- User's manual

## Application:

- Automotive
- Food industry
- Laboratory application

**Panel-mount thermometer** can be easily installed into a panel or can be used as a stand-alone unit.

## Comparable between ST-9290D-1 & ST-9290D-2



ST-9290D-1

- High temperature setting alarm
- Low temperature setting alarm
- °C/°F switchable
- ON/OFF switchable



ST-9290D-2

- High temperature setting alarm
- Low temperature setting alarm
- Memory Max/Min recalling
- ON/OFF switchable

